


CV 单向阀

CV Check Valve



产品介绍 Product Description

CV 单向阀主要介质为R134a或R1234yf。

The main medium of CV check valve is R134a or R1234yf.

产品特征及优势 Feature and Benefits

- 单向使用 / Unidirectional use
 - 正向施加压力关闭，反向施加压力打开；
Apply positive pressure to close and reverse pressure to open.
- 密封性好 / Good sealing
 - 使用橡胶密封，可靠性高；
Use rubber seal, high reliability.

产品应用 Product Application

CV单向阀，安装在系统中实现介质的单向流动；

The CV check valve, installed in the system to control the one-way flow of media.

操作 Operation

包装选项 Packaging Options

可提供定制包装以满足任何需要，请联系KESENS技术部了解详情。

Custom packaging can be provided to meet any need, please contact KESSENS Engineering for details.

技术参数 Technical Characteristics

项目ITEMS	参数PARAMETER
阀口直径 Valve Port Diameter	12mm
工作介质 Working Medium	R134a or R1234yf
环境温度 Ambient Temperature	-40°C~+125°C
工作温度 Temperature Range	-40°C~+125°C
外漏 External Leakage	≤1.5g/y @ 1.47MPa
内漏 Internal Leakage	≤10ml/min @ 1.03MPa
最大工作压力 Maximum Working Pressure	3.1MPa
最小开阀压差 Minimum opening valve pressure difference	≤10kPa
爆破压力 Burst Pressure	10.6MPa
寿命耐久 Lifetimes	>150,000 cycles@1.47MPa

可根据客户需求定制产品，如有需求请联系我们。
Customized products available upon request. Contact us for details.

地址：浙江省嘉兴市经济技术开发区天枢路199号
Add: No. 199, Tianshu Road, Economic and Technological Development Zone, Jiaxing City, Zhejiang Province, China.
电话 (Tel) : 0573-82858999
邮箱 (E-mail) : info@kesens.com
网址 (Web) : www.kesens.com

